



SZN25C
SZN35C



SZNA15
SZNA20



SFP50
SFP80



SM260
SM350

型号	Model	SZN25C	SZN35C	SZNA15	SZNA20
振动棒头	Vibration Head (mm)	25*420	35*420	28, 32, 38, 45, 50, 60	长470
频率	Vibration /min	13000-16000		9800-12000	
轴转速	Shaft roate speed	3000/3600			
振幅	Amplitude (m/min)	0.5		0.9	
软管长度	Flexible shaft (m)	1-2		3-6	
频率	Frequency (HZ)	50/60		50/60	
电机功率	Motor output (KW)	0.8		1.5	2.0
额定电压	Rated voltage (V)	220		220	
额定电流	Rated current (A)	3.6		6.85	9.1

型号	Model	SFP50	SFP80
出水口径	DiScharge Diameter (mm)	50	80
软管长度	Flexible shaft (m)	6	6
联轴器形式	Join type	日式PIN TYPE; 马式 BUTTERFLY TYPE	
最大升程	Max lift (m)	16	12
最大流量	Max delivery volume (m³/h)	25	40
发动机型号	Engine model	S20	
燃油箱容量	Fuel tank capacity (L)	3.8	3.8
启动系统	Starting system	手动反冲启动 Recoil starter	
包装尺寸	Packing size (L*W*H) mm	515*380*515	
净重	Net weight (KG)	22	24

Cement Mixers

型号	Model	SM260/SM350
发动机型号	Engine model	S178F(E)
输出功率	Rated output KW (HP)	4.9 (6.6)
容量	Drum Volume (L)	260/350
产量	Productivity (m³/h)	6-10/10-14
轮子数量	NO. wheel	2/4
滚筒转速	Speed of Mixing Drum (r/min)	30
启动系统	Starting system	手动反冲启动/电启动 Manual/Electric start
行进方式	Driving	手推 Manual push
包装尺寸	Packing size (L*W*H) mm	1900*900*1100/1960*940*1100
净重	Net weight (KG)	338/384