



S2000LG



**S1500
S2000**



S1500K



S4000



S10000DE/DE3



**S2000D (E)/D(E)3
S4000D (E)/D(E)3
S5000D (E)/D(E)3
S6500D (E)/D(E)3**



型号	Model	S1500	S2000	S4000	S1500K	S2000LG
型式	Type	有刷, 自励, 两级, 单相 Brush, Self-exciting, 2-pole, Single-phase				
频率	Frequency (HZ)	50/60	50/60	50/60	50/60	50/60
额定电压	Rated voltage (V)	110, 120, 220, 230, 240				
额定功率	Rated output KVA	1.3/1.5	1.7/2.0	2.6/3.0	1.3/1.5	1.7/2.0
最大功率	Max output KVA	1.5/1.8	2.0/2.4	3.0/3.5	1.5/1.7	2.0/2.4
噪音等级 (7米处)	Noise Level (7m) db	67	67	67	67	67
直流输出	DC output	12V-8.3A	12V-8.3A	12V-8.3A	12V-8.3A	12V-8.3A
功率因数	Power factor	1.0	1.0	1.0	1.0	1.0
断路保护器	Over current protector	无熔丝断路器 Fuseless circuit breaker				
发动机型号	Engine model	S20	S20	S28D	S20K	S20G
燃油箱容量	Fuel tank capacity (L)	15	15	15	15	-
连续工作时间	Continuous running time (hr)	13.5/11.2	11.7/10.4	8.0/7.0	10	-
启动系统	Starting system	手动反冲启动 Manual				
包装尺寸	Packing size (L*W*H) mm	585*425*530	585*425*530	650*460*605	585*425*530	585*440*530
净重	Net weight (KG)	40	41	58	45	40

Diesel Generator

型号	Model	S2000D(E) / S2000D(E) 3	S4000D(E) / S4000D(E) 3	S5000D(E) / S5000D(E) 3	S6500D(E) / S6500D(E) 3	S10000DE / S10000DE3
频率	Frequency (HZ)	50/60				
额定电压	Rated voltage (V)	110, 120, 220, 230, 240				220/380
额定功率	Rated output KVA	1.8/2.0	2.8/3.0	4.2/4.6	4.6/5.0	8.5/9.0
最大功率	Max output KVA	2.0/2.2	3.0/3.3	4.6/5.0	5.0/5.5	9.0/10.0
直流输出	DC output	12V-8.3A	12V-8.3A	12V-8.3A	12V-8.3A	12V-8.3A
功率因数	Power factor	1.0 / 0.8 (Three phase)				
噪音等级 (7米处)	Noise Level (7m) db (A)	77	77	77	77	80-83
发动机型号	Engine model	S170F(E)	S178F(E)	S186F(E)	S186FA(E)	SV840F
燃油箱容量	Fuel tank capacity (L)	12.5	12.5	12.5	12.5	25
连续工作时间	Continuous running time (hr)	14/12	9/8	6.5/5.5	6.0/5.0	12
启动系统	Starting system	手动反冲启动 / 电启动 Manual / Electric start				
包装尺寸	Packing size (L*W*H) mm	650*470*560	650*470*560	730*495*620	730*495*620	885*650*745
净重	Net weight (KG)	58	74	95	95	170