



Engine

Sinbest, sincerest and best partner

Engine

Sinbest, sincerest and best partner



S20



S160
S200



S28 B
S28 D
S32 B
S32 D



S20K



S20G

型号	Model	S28D	S28B	S32D	S32B	S20	S20K	S20G	S160	S200	
型式	Type	单缸, 四冲程, 侧阀, 风冷 Air-cooled, 4-cycle, single cylinder, side valve				单缸, 四冲程, 侧阀, 风冷 Air-cooled, 4-cycle, single cylinder, side valve			单缸, 四冲程, 顶置式气门, 风冷 Air-cooled, 4-cycle, single cylinder, OHV		
缸径*行程	Bore*stroke (mm)	75*62	75*62	77*67	77*67	67*52	67*52	67*52	68*45	68*54	
排量	Displacement (cm ³)	273	273	312	312	183	183	183	163	196	
额定输出功率	Rated output KW (HP) /rpm	4.2 (5.7) /3600	4.2 (5.7) /1800	4.7 (6.4) /3600	4.7 (6.4) /1800	2.65 (3.5) /3600	2.3 (3.1) /3600	2.85 (3.8) /3600	3.8 / 3600	4.3 / 3600	
最大输出功率	Max output KW (HP) /rpm	5.91 (8.0) /4000	5.91 (8.0) /2000	6.46 (8.8) /4000	6.46 (8.8) /2000	3.73 (5.0) /4000	3.2 (4.3) /4000	4.46 (6.0) /4000	4.1(5.5) / 4000	4.8(6.5) / 4000	
旋转方向	Direction of rotation	朝P.T.O逆时针 Counterclockwise, facing PTOshaft				朝P.T.O逆时针 Counterclockwise, facing PTOshaft					
燃油	Fuel	车用无铅汽油 Automobile Gasoline unleaded					煤油Kerosene (automobile gasoline when starting >90#)	液化气 Liquefied petroleum gas	车用无铅汽油 Automobile Gasoline unleaded		
燃油箱容量	Fuel tank capacity (L)	5.5	5.5	5.5	5.5	3.8	汽油GASOLINE 0.17 煤油KEROSENE 3.4	-	3.5	3.5	
机油容量	Lubricating oil capacity (L)	0.85	0.85	0.85	0.85	0.6	0.6	0.6	0.6	0.6	
火花塞	Spark Plug	E6TC	E6TC	E6TC	E6TC	E6TC	E6TC	E6TC	F7RTC	F7RTC	
启动系统	Starting system	手动反冲启动 Recoil starter					手动反冲启动 Recoil starter	手动反冲启动 Recoil starter	手动反冲启动 Recoil starter		
包装尺寸	Packing size (L*W*H) mm	440*380*460	445*380*490	440*380*460	445*380*490	380*370*425	380*370*425	380*370*360	380*370*425	380*370*360	
净重	Net weight (KG)	21.5	22	22.5	23	15	16	13	16	13	